

Extending the Built-In Solver

A new project automatically includes its own module that is loaded into the EUROPA engine and stub C++ files to hold custom code (see `makeproject`). Therefore, extending EUROPA components simply requires C++ code be added to those existing files. Consider the Example project [here](#), which can be downloaded with:

```
svn co https://babelfish.arc.nasa.gov/svn/europa/benchmarks/trunk/Example Example
```

Adding a Flaw Filter

Flaw filters determine what flaws shouldn't be considered by the solver. They use the solver matching rule syntax as well as any additional information contained in the planner configuration XML.

In order to create a new flaw filter, you must subclass the `FlawFilter` class and override the `FlawFilter::test` function. Because `FlawFilter` instances are created via a factory, the only argument your filter's constructor can take is a `const TiXmlElement&`, which will contain all of the available configuration information from the [planner configuration file](#). This XML data must be passed on to the base `FlawFilter` constructor along with a boolean flag indicating whether or not it's "dynamic"--the return value of `FlawFilter::test` may change during search.

Perhaps counterintuitively, the `FlawFilter::test` function should return true for any Entity to be filtered *out*. One way to think of this is that the function returns true if the Entity is "caught" by the filter.

Before it can be used in the [\[wiki:PlannerCfg planner configuration file\]](#), your filter must be registered as described in the [Component Registration](#) section.

Adding a Decision Point

Decision points manage the set of available choices for an individual flaw, the order of those choices, what the current choice is, and do the work of acting on the plan database when the choice is made and retracted. A decision point is created only when the solver actually picks a flaw to try to resolve, is revisited when the solver backtracks to that flaw, and is deleted when the solver backtracks past that flaw. If the flaw is revisited, a new decision point is created--the old one isn't reused.

If all that's wanted is some additional behavior beyond what the three basic Europa decision points ([\[source:PLASMA/trunk/src/PLASMA/Solvers/component/UnboundVariableDecisionPoint.hh unbound variable\]](#), [\[source:PLASMA/trunk/src/PLASMA/Solvers/component/ThreatDecisionPoint.hh threat\]](#), and [\[source:PLASMA/trunk/src/PLASMA/Solvers/component/OpenConditionDecisionPoint.hh open condition\]](#)) do, it's best to sub-class the decision point you want and override the parts that you want. If you want to:

-Change the choice order

- Override the constructor to do so "eagerly", by changing the actual order of the list of choices, if it's computed in the constructor.
- Override the `handleInitialize` function, to change the way the list of choices is computed.
- Override the `getNext` function to do so "lazily", by changing the way each next choice is gotten.

-Change the actions performed to make/un-make a decision

Override the `handleExecute` and/or `handleUndo` functions.

-Change when the choices are exhausted

Override the `hasNext` method.

If you're trying to write a decision point to resolve an entirely new kind of flaw, first read the section [\[#AddingaFlawManager? Adding a Flaw Manager\]](#) for information about writing a class to detect the new flaw type. Once you have a manager that detects the flaws, you'll have to create a sub-class of the base [\[source:PLASMA/trunk/src/PLASMA/Solvers/base/SolverDecisionPoint.hh SolverDecisionPoint?\]](#) class and provide the needed behaviors in the overrides described above.

Adding a Flaw Handler

(TODO)

Adding a Flaw Manager

(TODO)

Component Registration

The configuration model outlined [here](#) requires registration of concrete factories to link logical component names with actual C++ classes. This should be done in the `initialize()` method in the application's module. A macro is provided to make this quite straightforward. An example fragment of C++ code to register required components is provided below:

```
REGISTER_COMPONENT(``VariableFlawManager'',
                    EUROPA::VariableFlawManager);
REGISTER_COMPONENT(``StaticFilter'',
                    EUROPA::EUROPA::StaticFilter);
REGISTER_COMPONENT(``DynamicFilter'',
                    EUROPA::DynamicFilter);
REGISTER_COMPONENT(``InfiniteOrDynamic'',
                    EUROPA::InfiniteOrDynamicFilterCondition);
REGISTER_COMPONENT(``MinValue'',
                    EUROPA::MinValueHeuristic);
REGISTER_COMPONENT(``MaxValue'',
                    EUROPA::MaxValueHeuristic);
REGISTER_COMPONENT(``RandomValue'',
                    EUROPA::MonteCarloSelector);
```

TODO: Point to a specific example where we do this.